


LWAR Adapter / Size range from 1/8" to 2" / SS 304/304L, SS 316/316S / NPT, BSP, BSPT, UNF, ISO, SAE /
Female Pipe Adaptor / Forged Steel Compression Connector / Pipe Fittings Hex Reducing Bushing



-LWAR Adapter



Order information	T (NPT)	T1 (NPT)	L		D		W (HEX)	
			(in)	(mm)	(in)	(mm)	(in)	(mm)
-LWAR-2-1	1/8	1/16	1.03	26.2	0.19	4.8	0.43	11.1
-LWAR-4-2	1/4	1/8	1.06	26.9	0.28	7.1	0.56	14.2
-LWAR-6-2	3/8	1/8	0.86	21.8	0.34	8.6	0.68	17.4
-LWAR-6-4	3/8	1/4	1.19	30.2	0.37	9.5	0.75	19.0
-LWAR-8-2	1/2	1/8	1.08	27.4	0.34	8.6	0.87	22.2
-LWAR-8-4	1/2	1/4	1.08	27.4	0.45	11.4	0.87	22.2
-LWAR-8-6	1/2	3/8	1.41	35.8	0.47	11.9	0.87	22.2
-LWAR-12-4	3/4	1/4	1.08	27.4	0.45	11.4	1.06	27.0
-LWAR-12-6	3/4	3/8	1.08	27.4	0.59	15.0	1.06	27.0
-LWAR-12-8	3/4	1/2	1.63	41.4	0.62	15.7	1.06	27.0
-LWAR-16-4	1	1/4	1.37	34.8	0.45	11.4	1.38	35.1
-LWAR-16-6	1	3/8	1.37	34.8	0.59	15.0	1.38	35.1
-LWAR-16-8	1	1/2	1.37	34.8	0.73	18.5	1.38	35.1
-LWAR-16-12	1	3/4	1.85	47.0	0.88	22.4	1.38	35.1
-LWAR-20-8	1-1/4	1/2	1.46	37.1	0.73	18.5	1.75	44.4
-LWAR-20-12	1-1/4	3/4	1.47	37.3	0.94	23.9	1.75	44.4
-LWAR-20-16	1-1/4	1	1.94	49.3	1.17	29.7	1.75	44.4
-LWAR-24-8	1-1/2	1/2	1.61	40.9	0.73	18.5	2.13	54.0
-LWAR-24-12	1-1/2	3/4	1.61	40.9	0.94	23.9	2.13	54.0
-LWAR-24-16	1-1/2	1	1.61	40.9	1.17	29.7	2.13	54.0
-LWAR-24-20	1-1/2	1-1/4	2.31	58.7	1.50	38.1	2.13	54.0
-LWAR-32-8	2	1/2	1.83	46.5	0.73	18.5	2.74	70.0
-LWAR-32-12	2	3/4	1.83	46.5	0.94	23.9	2.74	70.0
-LWAR-32-16	2	1	1.83	46.5	1.17	29.7	2.74	70.0
-LWAR-32-20	2	1-1/4	1.83	46.5	1.50	38.1	2.74	70.0
-LWAR-32-24	2	1-1/2	1.83	46.5	1.73	43.9	2.74	70.0